



**MATERIAL SAFETY DATA SHEET**  
**High Pressure Laminate**  
**Static Dissipative**

**SECTION I - PRODUCT INFORMATION**

**PRODUCT NAME:**

Nevamar® High Pressure Decorative Laminate  
Static Dissipative Laminate -- Product Codes 720 & 740

**CHEMICAL NAME:**

Laminated Plastic

**CHEMICAL FORMULA:**

Not Applicable Due to Composite Nature of Product

**CHEMICAL FAMILY:**

Plastic Composite

**PRODUCT USE:**

Decorative Surface Covering with Static Dissipative Properties

**MANUFACTURER'S NAME AND ADDRESS:**

NEVAMAR COMPANY, LLC  
One Nevamar Place  
Hampton, SC 29924

**INFORMATION TELEPHONE NUMBER:**

Customer Service  
(803) 943-7200

**EMERGENCY TELEPHONE NUMBER:**

Chemtrec (800) 424-9300



**MATERIAL SAFETY DATA SHEET**  
**High Pressure Laminate**  
**Static Dissipative**

**SECTION II - HAZARDOUS COMPONENTS**

<u>COMPONENT</u> <u>(C.A.S. Registry Number)</u>	<u>WEIGHT</u> <u>PERCENT</u>	<u>OSHA</u> <u>PEL</u>	<u>ACGIH</u> <u>TLV</u>
---	---------------------------------	---------------------------	----------------------------

No hazardous substances according to 29 CFR 1910.1200.

Nuisance dust may be generated during machining, cutting or sanding operations. Nuisance dust is considered as "Particulates Not Otherwise Classified" or "Particulates Not Otherwise Regulated".

		<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Particulates Not Otherwise Classified or Regulated	---	TWA 15 mg/m <sup>3</sup> (Total Dust) STEL None	TWA 10 mg/m <sup>3</sup> (Inhalable Particulate) STEL None
Particulates Not Otherwise Classified or Regulated	---	TWA 5 mg/m <sup>3</sup> (Respirable Particulate) STEL None	TWA 3 mg/m <sup>3</sup> STEL None

**SECTION III - PHYSICAL PROPERTIES**

APPEARANCE AND ODOR:

Laminate sheet. No discernible odor.

MOLECULAR WEIGHT:

Not applicable due to composite nature of product.

SPECIFIC GRAVITY:

1.2 @ 70 F

SOLUBILITY IN WATER:

Insoluble in water.

pH:

Not applicable as product is solid.

**SECTION IV - FIRE AND EXPLOSION DATA:**

FLASH POINT:

Product has no flash point per Pensky Martins Closed Cup method.

FIRE EXTINGUISHING MEDIA:

This material is considered a "Class A" type combustible material. Use water, foam or dry chemical to extinguish.



**MATERIAL SAFETY DATA SHEET**  
**High Pressure Laminate**  
**Static Dissipative**

FLAMMABLE LIMITS: LOWER: None UPPER: None

SPECIAL FIRE FIGHTING PROCEDURES:

No special procedures required.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Minimize accumulation of dust from cutting or sanding operations through use of local ventilation systems. High airborne concentrations from dry fabrication operations may be explosive if contacted with an ignition source.

HAZARDOUS COMBUSTION PRODUCTS:

Thermal decomposition may release toxic and/or hazardous gases and airborne fibers.

**SECTION V - REACTIVITY DATA**

STABILITY:

Product is stable.

CONDITIONS TO AVOID:

Avoid exposure to temperatures above 450 F. Avoid exposure to open flame. Carbon fibers, dust and fibrous particles are electrically conductive and can cause shorting in electrical equipment. Explosive shorting of high voltage systems is possible.

INCOMPATIBILITY:

Store away from oxidizers, strong acids and strong bases.

HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition may release toxic and/or hazardous gases.

HAZARDOUS POLYMERIZATION:

Will not occur.

**SECTION VI - HEALTH HAZARD INFORMATION**

EXPOSURE FROM ROUTINE USE:

Dust from cutting or sanding operations can cause irritation to the eyes, respiratory system and skin.

EFFECTS OF OVEREXPOSURE:

Exposure to elevated dust levels may cause irritation to the eyes and respiratory system. Prolonged skin exposure to dust may cause drying of the skin.



# MATERIAL SAFETY DATA SHEET

## High Pressure Laminate

### Static Dissipative

#### ROUTES OF EXPOSURE:

Potential routes of exposure are inhalation as well as skin and eye contact.

#### EMERGENCY FIRST AID PROCEDURES:

**EYE CONTACT:** Wash eyes immediately with large amounts of water, occasionally lifting upper and lower lids, until no evidence of dust remains (approximately 15 - 20 minutes).

**SKIN CONTACT:** Wash affected area with soap and water to remove residual dust.

**INHALATION:** Remove from exposure to fresh air immediately.

**INGESTION:** Treat symptomatically and supportively if dust is ingested.

#### OTHER:

The resin used to make this plastic contains small amounts of formaldehyde. The cured plastic may evolve small amounts of formaldehyde when fabrication or heating of the product occurs. Air testing of representative fabrication operations indicates that formaldehyde releases are minimal and formaldehyde air concentrations are below regulatory standards. Formaldehyde has been identified as a skin sensitizer in low concentrations and as a probable human carcinogen (IARC-2A, pharyngeal cancer excess in formaldehyde exposed workers).

### **SECTION VII - TOXICITY DATA**

ORAL:	No data available.
DERMAL:	No data available.
INHALATION:	No data available.
EYE:	No data available.
CARCINOGENICITY:	Product has not been tested for carcinogenicity.

### **SECTION VIII - SPECIAL PROTECTION INFORMATION**

#### WORK AND HYGIENE PRACTICES:

Wear safety glasses or goggles in fabrication operations that may generate airborne dust. Wear gloves during exposure to dust or frequently wash hands to remove residual dust. Maintain airborne dust limits below the exposure limits. Minimize dust generation and accumulation from fabrication operations. Sweep up dust. Avoid blowing dust with compressed air. Avoid exposure of dust to open flame and ignition sources. Electrically ground and bond all equipment used for fabrication operations.

#### STORAGE AND HANDLING PRACTICES:

No special requirements for the product.

Store dust away from heat, ignition sources and oxidizing agents.



## MATERIAL SAFETY DATA SHEET High Pressure Laminate Static Dissipative

### PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:

Do not use compressed air to remove dust from equipment. Sweep or wash dust from unit.

### VENTILATION AND ENGINEERING CONTROLS:

Provide adequate general and local exhaust ventilation to maintain airborne concentrations below the exposure limits. Enclose fabrication operations, where possible, to minimize dust dispersion into other work areas.

### RESPIRATORY PROTECTION:

Where dust exposures may exceed the regulatory standards, respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respirator protection (Z88.2-1992).

### EYE PROTECTION:

Wear ANSI-approved safety glasses or goggles in fabrication operations that may generate airborne dust.

### HAND AND BODY PROTECTION:

To prevent drying of skin, wear gloves during exposure to dust or frequently wash hands to remove residual dust. Use hand lotion to moisten hands.

## **SECTION IX - SPILL, LEAK AND DISPOSAL PROCEDURES**

### IN CASE MATERIAL IS SPILLED OR RELEASED:

Dispose of dust or excess material according to applicable federal, state and local regulations.

## **SECTION X - REGULATORY INFORMATION**

DOT: Product not regulated by D.O.T.

Additional Requirements for State of California: Warning: Decorative laminate products contain formaldehyde, a substance known to the State of California to cause cancer. Laminates contain small amounts of residual formaldehyde that may be released in measurable quantities when stored in bulk quantities.



**MATERIAL SAFETY DATA SHEET**  
**High Pressure Laminate**  
**Static Dissipative**

Updated: 11/08  
Supersedes: 02/04

**IMPORTANT:** The information and data contained herein are believed to be accurate and have been compiled from sources believed to be accurate. All information contained herein is offered for your consideration, information, investigation and verification. NEVAMAR COMPANY MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY EXCLUDED. Nevamar Company will not be responsible for claims related to any parties' use of or reliance on information and data contained herein regardless of whether it is claimed that the information are inaccurate, incomplete, or otherwise misleading.